



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	60 L/min.
	8.6 mm
	Through
	2

OPTION SELECTION EXAMPLE: YCCSLHNAK

(L) (H) (N)

L	H	1000 - 4000 psi 25 psi (70 - 280 bar 1.) , 3000 psi (210 bar)	N
C	A	1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar) , 3000 psi (210 bar)	V
	B	400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar) 1000 psi (70 bar)	
	I	400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar) , 1000 psi (70 bar)	

PRIMARY CARTRIDGE

(A)

A	3:1 (with CBCA primary cartridge, 3:1,)
H	10:1 (with CBCHX primary cartridge, 10:1,)
G	4.5:1 (with CBCGX primary cartridge, 4.5:1,)
A	3:1 (with CBCAX primary cartridge, 3:1,)
H	10:1 (with CBCH primary cartridge, 10:1,)
G	4.5:1 (with CBCG primary cartridge, 4.5:1,)

INCLUDED COMPONENTS

Part	Description	Quantity
260-010*	Seat	1
340-002*	Pipe Plug	1
800-001-070*	Ball	1
CBCALHN	Cartridge - Primary	2
CXCDXCN	Cartridge	2