



### TECHNICAL DATA

Body Type	Line mount
Capacity	60 L/min.
Mounting Hole Diameter	8.6 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

**OPTION SELECTION EXAMPLE: YCCSLINAK**

CONTROL	(L) FUNCTIONAL SETTING RANGE	(I) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>I</b> 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set		<b>V</b> Viton	

**PRIMARY CARTRIDGE (A)**

<b>A</b>	3:1 (with CBCA primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula )
<b>H</b>	10:1 (with CBCHX primary cartridge, Ajuste fijo, proporción de pilotaje 10:1 , capacidad estándar contrabalance válvula )
<b>G</b>	4.5:1 (with CBCGX primary cartridge, Ajuste fijo, proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula )
<b>A</b>	3:1 (with CBCAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula )
<b>H</b>	10:1 (with CBCH primary cartridge, Proporción de pilotaje 10:1 , capacidad estándar contrabalance válvula )
<b>G</b>	4.5:1 (with CBCG primary cartridge, Proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula )

**INCLUDED COMPONENTS**

Part	Description	Quantity
260-010*	Seat	1
340-002*	Pipe Plug	1
800-001-070*	Ball	1
CBCALIN	Cartridge - Primary	2
CXCDXCN	Cartridge	2