



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	Eaton/Char-Lynn H & S

**CONFIGURATION OPTIONS**

**Model Code Example: YCCWLHNAK**

	(L)	(H)	(N)
<b>L</b>		<b>H</b>	<b>N</b>
<b>C</b>	-	1000 - 4000 psi 25 psi (70 - 280 bar 1.1), 3000 psi (210 bar)	<b>V</b>
		<b>A</b>	
		1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar)	
		<b>B</b>	
		400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar), 1000 psi (70 bar)	
		<b>I</b>	
		400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar), 1000 psi (70 bar)	

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	3:1 (with CBCA primary cartridge, 3:1, )
<b>H</b>	10:1 (with CBCHX primary cartridge, 10:1, )
<b>G</b>	4.5:1 (with CBCGX primary cartridge, 4.5:1, )
<b>A</b>	3:1 (with CBCAX primary cartridge, 3:1, )
<b>H</b>	10:1 (with CBCH primary cartridge, 10:1, )
<b>G</b>	4.5:1 (with CBCG primary cartridge, 4.5:1, )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CBCALHN	Cartridge - Primary	2
CSAAEXN	Cartridge	1
RDDALAN	Cartridge	2