



CONFIGURATION OPTIONS
Model Code Example: YCDCLANAJ

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
L	Standard Screw Adjustment	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	N	Buna-N
C	Tamper Resistant - Factory Set	B	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	V	Viton
F	Hex Head Screw with Locknut	C	150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting		
W	Hex Wrench Adjustment	D	25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
Y	manilla de tres agarres	E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
		N	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting		
		Q	60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting		
		W	150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE
(A)

A	4 psi (0,3 bar) (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
B	15 psi (1 bar) (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
C	30 psi (2 bar) (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
D	50 psi (3,5 bar) (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
E	75 psi (5 bar) (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
F	100 psi (7 bar) (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
Z	1 psi (0,07 bar) (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
Z	1 psi (0,07 bar) (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
F	100 psi (7 bar) (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
E	75 psi (5 bar) (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
D	50 psi (3,5 bar) (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
C	30 psi (2 bar) (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
B	15 psi (1 bar) (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
A	4 psi (0,3 bar) (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)

INCLUDED COMPONENTS

Part	Description	Quantity
CXDAXAN	Cartridge	1
RPECLAN	Cartridge - Primary	1