



CONFIGURATION OPTIONS

Model Code Example: YCEDLINAL

| CONTROL | (L) FUNCTIONAL SETTING RANGE | (I) SEAL MATERIAL | (N) |
|----------------------------------|---|-------------------|-----|
| L Standard Screw Adjustment | I 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting | N Buna-N | |
| C Tamper Resistant - Factory Set | | V Viton | |

PRIMARY CARTRIDGE

(A)

| | |
|---|---|
| A | 3:1 (with CBEA primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula) |
| H | 10:1 (with CBEHX primary cartridge,) |
| G | 4.5:1 (with CBEGX primary cartridge, Ajuste fijo, proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula) |
| A | 3:1 (with CBEAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula) |
| H | 10:1 (with CBEH primary cartridge, Proporción de pilotaje 10:1 , capacidad estándar contrabalance válvula) |
| G | 4.5:1 (with CBEG primary cartridge, Proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula) |

INCLUDED COMPONENTS

| Part | Description | Quantity |
|---------|---------------------|----------|
| CBEALIN | Cartridge - Primary | 2 |
| CXEDXCN | Cartridge | 2 |