



CONFIGURATION OPTIONS

Model Code Example: YCEGLINAL

CONTROL	(L) FUNCTIONAL SETTING RANGE	(I) SEAL MATERIAL	(N)
L Standard Screw Adjustment	400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set		V Viton	

PRIMARY CARTRIDGE

(A)

A	3:1 (with CBEA primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula)
H	10:1 (with CBEHX primary cartridge,)
Y	2:1 (with CBEYX primary cartridge, Ajuste fijo, proporción de pilotaje 2:1 , capacidad estándar contrabalance válvula)
G	4.5:1 (with CBEGX primary cartridge, Ajuste fijo, proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula)
A	3:1 (with CBEAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula)
Y	2:1 (with CBEY primary cartridge, Proporción de pilotaje 2:1 , capacidad estándar contrabalance válvula)
H	10:1 (with CBEH primary cartridge, Proporción de pilotaje 10:1 , capacidad estándar contrabalance válvula)
G	4.5:1 (with CBEG primary cartridge, Proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula)

INCLUDED COMPONENTS

Part	Description	Quantity
A330-006-004*	SAE Plug	1
CBEALIN	Cartridge - Primary	2
CSZNXXN	Cartridge	1
CXEDXAN	Cartridge	2
CXFAXAN	Cartridge	2