



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

安装孔直径	10,2 mm
安装孔深度	Through
安装孔数量	2

**CONFIGURATION OPTIONS**

**Model Code Example: YCENLHNAL**

控制方式	(L) 功能设定范围	(H) 密封材料	(N)
<b>L</b> 标准螺钉调节	<b>H</b> 1000 - 4000 psi 25 psi 单向阀开启 (70 - 280 bar 1.7 bar 单向阀开启), 3000 psi (210 bar) 标准设定值	<b>N</b> 丁腈橡胶 <b>V</b> 氟橡胶	

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	3:1 (with CBEA primary cartridge, 导压比 3:1, 标准型 平衡阀)
<b>H</b>	10:1 (with CBEHX primary cartridge, )
<b>G</b>	4.5:1 (with CBEGX primary cartridge, 固定设定, 导压比 4.5:1, 标准型 平衡阀)
<b>A</b>	3:1 (with CBEAX primary cartridge, 固定设定, 导压比 3:1, 标准型 平衡阀)
<b>H</b>	10:1 (with CBEH primary cartridge, 导压比 10:1, 标准型 平衡阀)
<b>G</b>	4.5:1 (with CBEG primary cartridge, 导压比 4.5:1, 标准型 平衡阀)

**INCLUDED COMPONENTS**

Part	Description	Quantity
CBEALHN	Cartridge - Primary	2
CXEDXCN	Cartridge	2