



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	120 L/min.
	10,2 mm
	Through
	2

**OPTION SELECTION EXAMPLE: YCENLHNAL**

(L) (H) (N)

<b>L</b>	<b>H</b>	1000 - 4000 psi 25 psi (70 - 280 bar 1. ) , 3000 psi (210 bar)	<b>N</b>
	<b>A</b>	1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar ) , 3000 psi (210 bar)	<b>V</b>

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	3:1 (with CBEA primary cartridge, 3:1, )
<b>H</b>	10:1 (with CBEHX primary cartridge, )
<b>G</b>	4.5:1 (with CBEGX primary cartridge, , 4.5:1, )
<b>A</b>	3:1 (with CBEAX primary cartridge, , 3:1, )
<b>H</b>	10:1 (with CBEH primary cartridge, 10:1, )
<b>G</b>	4.5:1 (with CBEG primary cartridge, 4.5:1, )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CBEALHN	Cartridge - Primary	2
CXEDXCN	Cartridge	2