



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	10,4 mm
	Through
	2

CONFIGURATION OPTIONS
Model Code Example: YCEPLHNL

(L)

(H)

(N)

L		H	1000 - 4000 psi 25 psi (70 - 280 bar 1.1), 3000 psi (210 bar)	N
C	-	A	1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar)	V

PRIMARY CARTRIDGE

(A)

A	3:1 (with CBEA primary cartridge, 3:1,)
H	10:1 (with CBEHX primary cartridge,)
Y	2:1 (with CBEYX primary cartridge, , 2:1,)
G	4.5:1 (with CBEGX primary cartridge, , 4.5:1,)
A	3:1 (with CBEAX primary cartridge, , 3:1,)
Y	2:1 (with CBEY primary cartridge, 2:1,)
H	10:1 (with CBEH primary cartridge, 10:1,)
G	4.5:1 (with CBEG primary cartridge, 4.5:1,)

INCLUDED COMPONENTS

Part	Description	Quantity
CBEALHN	Cartridge - Primary	2
CXEDXAN	Cartridge	2
CXFAXAN	Cartridge	2