



TECHNICAL DATA

Body Type	Line mount
Capacity	200 L/min.
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

OPTION SELECTION EXAMPLE: YCFCLANCJ

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	V Viton	
F Hex Head Screw with Locknut	C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting		
W Hex Wrench Adjustment	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
Y manilla de tres agarres	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
	N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting		
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting		
	W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE
(C)

C 30 psi (2 bar) (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
B 15 psi (1 bar) (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
D 50 psi (3,5 bar) (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
E 75 psi (5 bar) (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
F 100 psi (7 bar) (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
Z 1 psi (0,07 bar) (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
A 4 psi (0,3 bar) (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
A 4 psi (0,3 bar) (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula)
Z 1 psi (0,07 bar) (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
F 100 psi (7 bar) (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
E 75 psi (5 bar) (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
F 100 psi (7 bar) (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula)
D 50 psi (3,5 bar) (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula)
A 4 psi (0,3 bar) (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
B 15 psi (1 bar) (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula)
C 30 psi (2 bar) (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula)
B 15 psi (1 bar) (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
E 75 psi (5 bar) (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula)
C 30 psi (2 bar) (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)
Z 1 psi (0,07 bar) (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula)
D 50 psi (3,5 bar) (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)

INCLUDED COMPONENTS

Part	Description	Quantity
CXFAXCN	Cartridge	1
RPGCLAN	Cartridge - Primary	1