



### CONFIGURATION

<b>L</b> Control	Standard Screw Adjustment
<b>A</b> Adjustment Range	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting
<b>N</b> Seal Material	Buna-N
Range Letter(s) of	30 psi (2 bar) (with RDFA
<b>C</b> Subordinate Cartridge	primary cartridge, Acción-directa alivio válvula )

### TECHNICAL DATA

Body Type	apilables	NOTE: DATA
Capacity	120 L/min.	MAY VARY
Body Features	Out of A	BY
Seal Plate Included (see notes)	No	
Stack Height	63 mm	
Mounting Hole Diameter	7,1 mm	
Mounting Hole Depth	Through	
Mounting Hole Quantity	4	

CONFIGURATION. SEE CONFIGURATION SECTION.

**OPTION SELECTION EXAMPLE: YCFLANC**

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>A</b> 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set	<b>C</b> 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting	<b>V</b> Viton	
<b>K</b> manilla	<b>D</b> 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting		
	<b>E</b> 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting		
	<b>S</b> 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) Standard Setting		
	<b>W</b> 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting		

**PRIMARY CARTRIDGE** (C)

<b>C</b> 30 psi (2 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>A</b> 4 psi (0,3 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>B</b> 15 psi (1 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>D</b> 50 psi (3,5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>E</b> 75 psi (5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>F</b> 100 psi (7 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>Z</b> 1 psi (0,07 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )
<b>Z</b> 1 psi (0,07 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>F</b> 100 psi (7 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>E</b> 75 psi (5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>D</b> 50 psi (3,5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>C</b> 30 psi (2 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>B</b> 15 psi (1 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )
<b>A</b> 4 psi (0,3 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )