



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                                 |            |
|---------------------------------|------------|
| Body Type                       | apilables  |
| Interface                       | ISO 05     |
| Body Features                   | fuera de B |
| Seal Plate Included (see notes) | Yes        |
| Stack Height                    | 63 mm      |
| Mounting Hole Diameter          | 7,1 mm     |
| Mounting Hole Depth             | Through    |
| Mounting Hole Quantity          | 4          |

**CONFIGURATION OPTIONS**

**Model Code Example: YCFMLANCA**

| CONTROL                            | (L) ADJUSTMENT RANGE                                                        | (A) SEAL MATERIAL | (N) |
|------------------------------------|-----------------------------------------------------------------------------|-------------------|-----|
| <b>L</b> Standard Screw Adjustment | <b>A</b> 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting  | <b>N</b> Buna-N   |     |
|                                    | <b>B</b> 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) Standard Setting  | <b>V</b> Viton    |     |
|                                    | <b>C</b> 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting |                   |     |
|                                    | <b>D</b> 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting     |                   |     |
|                                    | <b>E</b> 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting      |                   |     |
|                                    | <b>S</b> 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) Standard Setting      |                   |     |
|                                    | <b>W</b> 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting  |                   |     |

**PRIMARY CARTRIDGE**

(C)

|                                                                                                       |
|-------------------------------------------------------------------------------------------------------|
| <b>C</b> 30 psi (2 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )                 |
| <b>A</b> 4 psi (0,3 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )                |
| <b>B</b> 15 psi (1 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )                 |
| <b>D</b> 50 psi (3,5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )               |
| <b>E</b> 75 psi (5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )                 |
| <b>F</b> 100 psi (7 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )                |
| <b>Z</b> 1 psi (0,07 bar) (with RDFA primary cartridge, Acción-directa alivio válvula )               |
| <b>Z</b> 1 psi (0,07 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula ) |
| <b>F</b> 100 psi (7 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )  |
| <b>E</b> 75 psi (5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )   |
| <b>D</b> 50 psi (3,5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula ) |
| <b>C</b> 30 psi (2 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )   |
| <b>B</b> 15 psi (1 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )   |
| <b>A</b> 4 psi (0,3 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula )  |

**INCLUDED COMPONENTS**

| Part         | Description         | Quantity |
|--------------|---------------------|----------|
| 500-001-014* | O-Ring              | 5        |
| 700-001*     | Seal Plate          | 1        |
| CXFAXCN      | Cartridge           | 1        |
| RDFALAN      | Cartridge - Primary | 1        |