



TECHNICAL DATA

Body Type	apilables
Interface	ISO 05 - X&Y
Body Features	fuera de B
Seal Plate Included (see notes)	No
Stack Height	63 mm
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	4

CONFIGURATION

L Control	Standard Screw Adjustment
A Adjustment Range	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting
N Seal Material	Buna-N
C Subordinate Cartridge	30 psi (2 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)

CONFIGURATION OPTIONS

Model Code Example: YCFNLANC

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
L	Standard Screw Adjustment	A	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N	Buna-N
C	Tamper Resistant - Factory Set	C	1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting	V	Viton
K	manilla	D	200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting		
		E	100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting		
		S	50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) Standard Setting		
		W	800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE

(C)

C	30 psi (2 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)
A	4 psi (0,3 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)
B	15 psi (1 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)
D	50 psi (3,5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)
E	75 psi (5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)
F	100 psi (7 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)
Z	1 psi (0,07 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)
Z	1 psi (0,07 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)
F	100 psi (7 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)
E	75 psi (5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)
D	50 psi (3,5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)
C	30 psi (2 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)
B	15 psi (1 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)
A	4 psi (0,3 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)