



CONFIGURATION

L Control	Standard Screw Adjustment
A Adjustment Range	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting
N Seal Material	Buna-N
C Subordinate Cartridge	30 psi (2 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)

TECHNICAL DATA

Body Type	Sandwich
Interface	ISO 05 - X&Y
Capacity	120 L/min.
Body Features	Out of B
Seal Plate Included (see notes)	No
Stack Height	63 mm
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	4

OPTION SELECTION EXAMPLE: YCFNLANC

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set	B 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) Standard Setting	V Viton	
	C 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting		
	D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting		
	E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting		
	S 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) Standard Setting		
	W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting		
PRIMARY CARTRIDGE			(C)
C 30 psi (2 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)			
A 4 psi (0,3 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)			
B 15 psi (1 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)			
D 50 psi (3,5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)			
E 75 psi (5 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)			
F 100 psi (7 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)			
Z 1 psi (0,07 bar) (with RDFA primary cartridge, Acción-directa alivio válvula)			
Z 1 psi (0,07 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)			
F 100 psi (7 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)			
E 75 psi (5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)			
D 50 psi (3,5 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)			
C 30 psi (2 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)			
B 15 psi (1 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)			
A 4 psi (0,3 bar) (with RDFA3 primary cartridge, No-ajustable acción-directa alivio válvula)			