



**CONFIGURATION**

<b>L</b>	
<b>A</b>	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)
<b>N</b>	
<b>C</b>	Range Letter(s) of Subordinate Cartridge      30 psi (2 bar) (with RDFA primary cartridge, )

**TECHNICAL DATA**

		NOTE:
		DATA
		MAY
	ISO 05 - X&Y	VARY
	120 L/min.	BY
Stack Height	63 mm	
( )		
	Out of B	
	7,1 mm	
	Through	
	4	

CONFIGURATION. SEE CONFIGURATION SECTION.

**OPTION SELECTION EXAMPLE: YCFNLANC**

(L)	(A)	(N)
<b>L</b>	<b>A</b> 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) <b>B</b> 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) <b>C</b> 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) <b>D</b> 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) <b>E</b> 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) <b>S</b> 50 - 200 psi (3,5 - 14 bar), 100 psi (7 bar) <b>W</b> 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar)	<b>N</b> V

**PRIMARY CARTRIDGE**

(C)

<b>C</b>	30 psi (2 bar) (with RDFA primary cartridge, )
<b>A</b>	4 psi (0,3 bar) (with RDFA primary cartridge, )
<b>B</b>	15 psi (1 bar) (with RDFA primary cartridge, )
<b>D</b>	50 psi (3,5 bar) (with RDFA primary cartridge, )
<b>E</b>	75 psi (5 bar) (with RDFA primary cartridge, )
<b>F</b>	100 psi (7 bar) (with RDFA primary cartridge, )
<b>Z</b>	1 psi (0,07 bar) (with RDFA primary cartridge, )
<b>Z</b>	1 psi (0,07 bar) (with RDFA3 primary cartridge, )
<b>F</b>	100 psi (7 bar) (with RDFA3 primary cartridge, )
<b>E</b>	75 psi (5 bar) (with RDFA3 primary cartridge, )
<b>D</b>	50 psi (3,5 bar) (with RDFA3 primary cartridge, )
<b>C</b>	30 psi (2 bar) (with RDFA3 primary cartridge, )
<b>B</b>	15 psi (1 bar) (with RDFA3 primary cartridge, )
<b>A</b>	4 psi (0,3 bar) (with RDFA3 primary cartridge, )