



TECHNICAL DATA

	13,5 mm
	Through
	2

CONFIGURATION

L	
H	1000 - 4000 psi 25 psi (70 - 280 bar 1.7 bar), 3000 psi (210 bar)
N	
A	Pilot Ratio (4th Letter) of Primary Cartridge 3:1 (with CBGA primary cartridge, 3:1,)
M	Port and Material Designation Ports C1,C2,V1,V2 — SAE 16; Port T — SAE 16; Aluminum

CONFIGURATION OPTIONS
Model Code Example: YCGELHNAM

(L)	(H)	(N)
L	H 1000 - 4000 psi 25 psi (70 - 280 bar 1.1), 3000 psi (210 bar)	N
C -	A 1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar)	V
	B 400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar), 1000 psi (70 bar)	
	I 400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar), 1000 psi (70 bar)	

PRIMARY CARTRIDGE
(A)

A	3:1 (with CBGA primary cartridge, 3:1,)
H	10:1 (with CBGH primary cartridge, 10:1,)
G	4.5:1 (with CBGG primary cartridge, 4.5:1,)

INCLUDED COMPONENTS

Part	Description	Quantity
CBGALHN	Cartridge - Primary	2
CXGDXAN	Cartridge	2
CXHAXAN	Cartridge	2