



**TECHNICAL DATA**

NOTE:

		DATA
		MAY
	240 L/min.	VARY
	13,5 mm	BY
	Through	
	2	

**CONFIGURATION**

<b>L</b>	1000 - 4000 psi 25 psi (70 - 280 bar 1.7 bar), 3000 psi (210 bar)
<b>H</b>	
<b>N</b>	
<b>A</b>	Pilot Ratio (4th Letter) of Primary Cartridge: 3:1 (with CBGA primary cartridge, 3:1)
<b>M</b>	Port and Material Designation: Ports C1,C2,V1,V2 — SAE 16; Port T — SAE 16; Aluminum

CONFIGURATION. SEE CONFIGURATION SECTION.

**OPTION SELECTION EXAMPLE: YCGELHNM**

(L) (H) (N)

<b>L</b>	<b>H</b>	1000 - 4000 psi 25 psi (70 - 280 bar 1. ) , 3000 psi (210 bar)	<b>N</b>
<b>C</b>	<b>A</b>	1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar ) , 3000 psi (210 bar)	<b>V</b>
	<b>B</b>	400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar ) 1000 psi (70 bar)	
	<b>I</b>	400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar ) , 1000 psi (70 bar)	

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	3:1 (with CBGA primary cartridge, 3:1, )
<b>H</b>	10:1 (with CBGH primary cartridge, 10:1, )
<b>G</b>	4.5:1 (with CBGG primary cartridge, 4.5:1, )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CBGALHN	Cartridge - Primary	2
CXGDXAN	Cartridge	2
CXHAXAN	Cartridge	2