



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                        |                      |
|------------------------|----------------------|
| Body Type              | montaje en línea     |
| Capacity               | 480 L/min.           |
| Mounting Hole Thread   | .500-13 UNC - 2B in. |
| Mounting Hole Depth    | 19 mm                |
| Mounting Hole Quantity | 4                    |

**OPTION SELECTION EXAMPLE: YCJDLHNR**

| CONTROL                                 | (L) FUNCTIONAL SETTING RANGE   | (H) SEAL MATERIAL | (N) |
|---|--|-------------------|-----|
| <b>L</b> Standard Screw Adjustment      | <b>H</b> 1000 - 4000 psi w/25 psi Check (70 - 280 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting | <b>N</b> Buna-N   |     |
| <b>C</b> Tamper Resistant - Factory Set | <b>A</b> 1000 - 4000 psi w/4 psi Check (70 - 280 bar w/ 0,3 bar Check), 3000 psi (210 bar) Standard Setting  | <b>V</b> Viton    |     |
|   | <b>B</b> 400 - 1500 psi w/4 psi Check (28 - 105 bar w/ 0,3 bar Check), 1000 psi (70 bar) Standard Setting    |                   |     |

**PRIMARY CARTRIDGE (A)**

|  |
|--|
| <b>A</b> 3:1 (with CBIA primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula )     |
| <b>H</b> 10:1 (with CBIH primary cartridge, Proporción de pilotaje 10:1 , capacidad estándar contrabalance válvula )   |
| <b>G</b> 4.5:1 (with CBIG primary cartridge, Proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula ) |

**INCLUDED COMPONENTS**

| Part    | Description         | Quantity |
|---------|---------------------|----------|
| CBIALHN | Cartridge - Primary | 2        |
| CXIDXCN | Cartridge           | 2        |