



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	480 L/min.
	.500-13 UNC - 2B in.
	19 mm
	4

**OPTION SELECTION EXAMPLE: YCJDLHNR**

(L)	(H)	(N)
<b>L</b>	<b>H</b>	<b>N</b>
<b>C</b>	1000 - 4000 psi 25 psi (70 - 280 bar 1. ), 3000 psi (210 bar)	<b>V</b>
	<b>A</b>	
	1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar ), 3000 psi (210 bar)	
	<b>B</b>	
	400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar ), 1000 psi (70 bar)	
	<b>I</b>	
	400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar ), 1000 psi (70 bar)	

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	3:1 (with CBIA primary cartridge, 3:1, )
<b>H</b>	10:1 (with CBIH primary cartridge, 10:1, )
<b>G</b>	4.5:1 (with CBIG primary cartridge, 4.5:1, )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CBIALHN	Cartridge - Primary	2
CXIDXCN	Cartridge	2