



### TECHNICAL DATA

Body Type	Line mount
Capacity	60 L/min.
Mounting Hole Diameter	8.6 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

**OPTION SELECTION EXAMPLE: YDCELINAK**

CONTROL	(L) FUNCTIONAL SETTING RANGE	(I) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>I</b> 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	<b>(N)</b>
<b>C</b> Tamper Resistant - Factory Set		<b>V</b> Viton	
<b>PRIMARY CARTRIDGE</b>			<b>(A)</b>
<b>A</b> A (with CBCY primary cartridge, Proporción de pilotaje 2:1 , capacidad estándar contrabalance válvula )			
<b>A</b> A (with CBCYX primary cartridge, Ajuste fijo, proporción de pilotaje 2:1 , capacidad estándar contrabalance válvula )			

**INCLUDED COMPONENTS**

Part	Description	Quantity
CBCYLIN	Cartridge - Primary	1
CODAXEN	Cartridge	1