



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	apilables
Interface	ISO 03
Body Features	alimentación regulada en P
Seal Plate Included (see notes)	No
Stack Height	43,2 mm

CONFIGURATION OPTIONS

Model Code Example: YDCLLFNCA

CONTROL	(L) MAXIMUM ORIFICE DIAMETER	(F) SEAL MATERIAL	(N)
L Standard Screw Adjustment	F .33 in. (8,4 mm)	N Buna-N	
H Calibrated Handknob with Detent Lock		V Viton	
K manilla			

PRIMARY CARTRIDGE

(C)

C 30 psi (2 bar) (with NFCD primary cartridge, Totalmente ajustable aguja válvula)
A 4 psi (0,3 bar) (with NFCD primary cartridge, Totalmente ajustable aguja válvula)
B 15 psi (1 bar) (with NFCD primary cartridge, Totalmente ajustable aguja válvula)
D 50 psi (3,5 bar) (with NFCD primary cartridge, Totalmente ajustable aguja válvula)
E 75 psi (5 bar) (with NFCD primary cartridge, Totalmente ajustable aguja válvula)
F 100 psi (7 bar) (with NFCD primary cartridge, Totalmente ajustable aguja válvula)
Z 1 psi (0,07 bar) (with NFCD primary cartridge, Totalmente ajustable aguja válvula)

INCLUDED COMPONENTS

Part	Description	Quantity
300-002-008*	Screw	4
350-023*	Studnut	4
500-001-012*	O-Ring	4
811-001-006*	Pin	1
CXDAXCN	Cartridge	1
NFCDLFN	Cartridge - Primary	1