



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	apiliables
Interface	ISO 05
Seal Plate Included (see notes)	No
Stack Height	49 mm

CONFIGURATION OPTIONS

Model Code Example: YDEELHNB

CONTROL	(L) FUNCTIONAL SETTING RANGE	(H) SEAL MATERIAL	(N)
L Standard Screw Adjustment	H 1000 - 4000 psi w/25 psi Check (70 - 280 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set	A 1000 - 4000 psi w/4 psi Check (70 - 280 bar w/ 0,3 bar Check), 3000 psi (210 bar) Standard Setting	V Viton	
	B 400 - 1500 psi w/4 psi Check (28 - 105 bar w/ 0,3 bar Check), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE

(B)

B	B (with CBEJ primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula)
B	B (with CBEJX primary cartridge,)

INCLUDED COMPONENTS

Part	Description	Quantity
340-001*	Pipe Plug	2
500-001-014*	O-Ring	5
CBEJLHN	Cartridge - Primary	1
COFAXEN	Cartridge	1