



## TECHNICAL DATA

Body Type	Sandwich
Interface	ISO 05 - X&Y
Capacity	95 L/min.
Body Features	B to A
Seal Plate Included (see notes)	No
Stack Height	63 mm
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	4

**OPTION SELECTION EXAMPLE: YDELLINBB**

CONTROL	(L) FUNCTIONAL SETTING RANGE	(I) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>I</b> 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	<b>(N)</b>
<b>C</b> Tamper Resistant - Factory Set		<b>V</b> Viton	
<b>PRIMARY CARTRIDGE</b>			<b>(B)</b>
<b>B</b> B (with CBEJ primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula )			
<b>B</b> B (with CBEJX primary cartridge, )			

**INCLUDED COMPONENTS**

Part	Description	Quantity
340-001*	Pipe Plug	2
CBEJLIN	Cartridge - Primary	1
COFAXEN	Cartridge	1