



in.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                               |          |
|-------------------------------|----------|
| Body Type                     | subplaca |
| Interface                     | ISO 05   |
| Mounting Hole Diameter        | 10,4 mm  |
| Mounting Hole C'bore Diameter | 15,0 mm  |
| Mounting Hole C'bore Depth    | 14,2 mm  |
| Mounting Hole Quantity        | 2        |

**CONFIGURATION OPTIONS**

Model Code Example: **YDEMLHNBL**

| CONTROL                                 | (L) FUNCTIONAL SETTING RANGE   | (H) SEAL MATERIAL | (N) |
|---|--|-------------------|-----|
| <b>L</b> Standard Screw Adjustment      | <b>H</b> 1000 - 4000 psi w/25 psi Check (70 - 280 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting | <b>N</b> Buna-N   |     |
| <b>C</b> Tamper Resistant - Factory Set | <b>A</b> 1000 - 4000 psi w/4 psi Check (70 - 280 bar w/ 0,3 bar Check), 3000 psi (210 bar) Standard Setting  | <b>V</b> Viton    |     |
|   | <b>B</b> 400 - 1500 psi w/4 psi Check (28 - 105 bar w/ 0,3 bar Check), 1000 psi (70 bar) Standard Setting    |                   |     |

**PRIMARY CARTRIDGE**

(B)

|          |   |
|----------|---|
| <b>B</b> | B (with CBEA primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula )               |
| <b>B</b> | B (with CBEAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula ) |

**INCLUDED COMPONENTS**

| Part    | Description         | Quantity |
|---------|---------------------|----------|
| CBEALHN | Cartridge - Primary | 1        |
| COFAXEN | Cartridge           | 1        |
| RPECLAN | Cartridge           | 1        |