



**TECHNICAL DATA**

NOTE:  
DATA  
MAY  
VARY  
BY

	ISO 05
	120 L/min.
Stack Height	63 mm
( )	
	0 - 12 gpm
	Meter in on B or meter out on A

**CONFIGURATION**

L	
A	.1 - 12 gpm (0,4 - 45 L/min.)
N	
B	Primary Cartridge B (with FXDA primary cartridge, )
A	Port and Material Designation A Aluminum

CONFIGURATION. SEE CONFIGURATION SECTION.

**OPTION SELECTION EXAMPLE: YFECLANBA**

(L) (A) (N)

<b>L</b>	<b>A</b>	.1 - 12 gpm (0,4 - 45 L/min.)	<b>N</b>
X	B	.1 - 12 gpm (0,4 - 45 L/min.)	V
	I	( ) 17 gpm (64 L/min.)	

**PRIMARY CARTRIDGE**
**(B)**

<b>B</b>	B (with FXDA primary cartridge, )
B	B (with FXDA8 primary cartridge, , T-8A )

**INCLUDED COMPONENTS**

Part	Description	Quantity
500-001-014*	O-Ring	5
700-001*	Seal Plate	1
CKIEVCN	Cartridge	1
FXDALAN	Cartridge - Primary	1