



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	aplilables
Interface	ISO 05
Body Features	Meter in on B or meter out on A
Control Flow Range	0 - 12 gpm
Seal Plate Included (see notes)	Yes
Stack Height	63 mm

CONFIGURATION OPTIONS

Model Code Example: YFECXANBA

CONTROL	(X)	SETTING RANGE	(A)	SEAL MATERIAL	(N)
X	Not Adjustable	A	Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)	N	Buna-N
C	Tamper Resistant - Factory Set	B	Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)	V	Viton
K	manilla	I	Incomplete (no orifice) 17 gpm (64 L/min.)		
L	Tuning Adjustment				

PRIMARY CARTRIDGE

(B)

B	B (with FXDA primary cartridge, Fixed-orifice, compensado por presión control de caudal válvula)
B	B (with FXDA8 primary cartridge, De venteo fixed-orifice, compensado por presión control de caudal válvula con cavidad de control T-8A integral)

INCLUDED COMPONENTS

Part	Description	Quantity
500-001-014*	O-Ring	5
700-001*	Seal Plate	1
CKIEVCN	Cartridge	1
FXDAXAN	Cartridge - Primary	1