



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	aplilables
Interface	ISO 05
Capacity	120 L/min.
Body Features	Meter in on B or meter out on A
Control Flow Range	0 - 12 gpm
Seal Plate Included (see notes)	Yes
Stack Height	63 mm

**OPTION SELECTION EXAMPLE: YFECXANBA**

CONTROL	(X) SETTING RANGE	(A) SEAL MATERIAL	(N)
<b>X</b> Not Adjustable	<b>A</b> Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)	<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set	<b>B</b> Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)	<b>V</b> Viton	
<b>K</b> manilla	<b>I</b> Incomplete (no orifice) 17 gpm (64 L/min.)		
<b>L</b> Tuning Adjustment			

**PRIMARY CARTRIDGE** **(B)**

<b>B</b>	B (with FXDA primary cartridge, Fixed-orifice, compensado por presión control de caudal válvula )
<b>B</b>	B (with FXDA8 primary cartridge, De venteo fixed-orifice, compensado por presión control de caudal válvula con cavidad de control T-8A integral )

**INCLUDED COMPONENTS**

Part	Description	Quantity
500-001-014*	O-Ring	5
700-001*	Seal Plate	1
CKIEVCN	Cartridge	1
FXDAXAN	Cartridge - Primary	1