



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|------------------------|------------------|
| Body Type | montaje en línea |
| Control Flow Range | 0 - 12 gpm |
| Mounting Hole Diameter | 10,4 mm |
| Mounting Hole Depth | Through |
| Mounting Hole Quantity | 2 |

CONFIGURATION OPTIONS

Model Code Example: YFEFXANAL

| CONTROL | (X) | SETTING RANGE | (A) | SEAL MATERIAL | (N) |
|----------|--------------------------------|---------------|---|---------------|--------|
| X | Not Adjustable | A | Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.) | N | Buna-N |
| C | Tamper Resistant - Factory Set | B | Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.) | V | Viton |
| K | manilla | I | Incomplete (no orifice) 17 gpm (64 L/min.) | | |
| L | Tuning Adjustment | | | | |

PRIMARY CARTRIDGE

(A)

| | |
|----------|---|
| A | A (with FRDA primary cartridge, Fixed-orifice, desvió / restrictivo, prioritario, control de caudal válvula) |
|----------|---|

INCLUDED COMPONENTS

| Part | Description | Quantity |
|---------|---------------------|----------|
| FRDAXAN | Cartridge - Primary | 1 |
| RPECFAN | Cartridge | 1 |