



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                                 |                                 |
|---------------------------------|---------------------------------|
| Body Type                       | aplilables                      |
| Interface                       | ISO 05                          |
| Capacity                        | 120 L/min.                      |
| Body Features                   | Meter in on B or meter out on A |
| Control Flow Range              | 0 - 12 gpm                      |
| Seal Plate Included (see notes) | Yes                             |
| Stack Height                    | 63 mm                           |

**OPTION SELECTION EXAMPLE: YFEULANBA**

| CONTROL                            | (L) ADJUSTMENT RANGE                   | (A) SEAL MATERIAL | (N) |
|------------------------------------|--|-------------------|-----|
| <b>L</b> Standard Screw Adjustment | <b>A</b> .2 - 12 gpm (0,8 - 45 L/min.) | <b>N</b> Buna-N   |     |
|                                    | <b>B</b> .2 - 3 gpm (0,8 - 11 L/min.)  | <b>V</b> Viton    |     |

**PRIMARY CARTRIDGE** **(B)**

|   |
|---|
| <b>B</b> B (with FDCB primary cartridge, Totalmente ajustable compensado por presión control de caudal válvula con anti-retorno de caudal inverso ) |
|---|

**INCLUDED COMPONENTS**

| Part         | Description         | Quantity |
|--------------|---------------------|----------|
| 500-001-014* | O-Ring              | 5        |
| 700-001*     | Seal Plate          | 1        |
| CKEHSCN      | Cartridge           | 1        |
| FDCBLAN      | Cartridge - Primary | 1        |