



Flow Control, Priority Flow On A, Bypass to T,  
Reverse Free Flow Check

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	aplilables
Interface	ISO 05 - X&Y
Body Features	Meter in A
Control Flow Range	0 - 12 gpm
Seal Plate Included (see notes)	Yes
Stack Height	63 mm

**CONFIGURATION OPTIONS**

**Model Code Example: YFEXXANB**

CONTROL		(X) SETTING RANGE	(A) SEAL MATERIAL	(N)
<b>X</b>	Not Adjustable	<b>A</b>	Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)	<b>N</b>
<b>C</b>	Tamper Resistant - Factory Set	<b>B</b>	Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)	<b>V</b>
<b>K</b>	manilla	<b>I</b>	Incomplete (no orifice) 17 gpm (64 L/min.)	
<b>L</b>	Tuning Adjustment			
<b>PRIMARY CARTRIDGE</b>				<b>(B)</b>
<b>B</b>	B (with FRDA primary cartridge, Fixed-orifice, desvió /restrictivo, prioritario, control de caudal válvula )			