



### TECHNICAL DATA

Body Type	Sandwich
Interface	ISO 05
Capacity	120 L/min.
Body Features	Meter in on A or meter out on B
Control Flow Range	0 - 12 gpm
Seal Plate Included (see notes)	Yes
Stack Height	63 mm

**OPTION SELECTION EXAMPLE: YFEZLANBA**

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>A</b> .2 - 12 gpm (0,8 - 45 L/min.)	<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set	<b>B</b> .2 - 3 gpm (0,8 - 11 L/min.)	<b>V</b> Viton	
<b>Y</b> manilla de tres agarres			

**PRIMARY CARTRIDGE (B)**

<b>B</b> B (with FDCB primary cartridge, Totalmente ajustable compensado por presión control de caudal válvula con anti-retorno de caudal inverso )
---

**INCLUDED COMPONENTS**

Part	Description	Quantity
500-001-014*	O-Ring	5
700-001*	Seal Plate	1
CKEHSCN	Cartridge	1
FDCBLAN	Cartridge - Primary	1