



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---------------------------------|------------|
| Body Type | aplilables |
| Interface | ISO 08 |
| Body Features | Meter in A |
| Control Flow Range | 0 - 30 gpm |
| Seal Plate Included (see notes) | No |
| Stack Height | 87 mm |

CONFIGURATION OPTIONS

Model Code Example: YFGCLENCA

| CONTROL | (L) | MAXIMUM ORIFICE DIAMETER | (E) | SEAL MATERIAL | (N) |
|----------|--------------------------------------|--------------------------|------------------|---------------|--------|
| L | Standard Screw Adjustment | E | .38 in. (9,7 mm) | N | Buna-N |
| H | Calibrated Handknob with Detent Lock | F | .28 in. (7,1 mm) | V | Viton |
| K | manilla | | | | |

PRIMARY CARTRIDGE

(C)

| | |
|----------|--|
| C | C (with NFEC primary cartridge, Totalmente ajustable aguja válvula) |
|----------|--|

INCLUDED COMPONENTS

| Part | Description | Quantity |
|--------------|---------------------|----------|
| 340-001* | Pipe Plug | 1 |
| 340-003* | Pipe Plug | 1 |
| 500-001-114* | O-Ring | 2 |
| 500-001-121* | O-Ring | 4 |
| 811-001-002* | Locating Pin | 1 |
| CKGBPCN | Cartridge | 1 |
| NFECLEN | Cartridge - Primary | 1 |