



CONFIGURATION OPTIONS
Model Code Example: YFRCLANAL

| CONTROL | | (L) ADJUSTMENT RANGE | (A) SEAL MATERIAL | (N) |
|----------|--------------------------------|--|-------------------|-----|
| L | Standard Screw Adjustment | A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting | N Buna-N | |
| C | Tamper Resistant - Factory Set | B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting | V Viton | |
| F | Hex Head Screw with Locknut | C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting | | |
| W | Hex Wrench Adjustment | D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting | | |
| Y | manilla de tres agarres | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting | | |
| | | N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting | | |
| | | Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting | | |
| | | W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting | | |

PRIMARY CARTRIDGE
(A)

| | |
|----------|---|
| A | A (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula) |
| A | A (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula) |
| A | A (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral) |

INCLUDED COMPONENTS

| Part | Description | Quantity |
|--------------|---------------------|----------|
| 500-001-113* | O-Ring | 2 |
| 500-001-125* | O-Ring | 1 |
| CXFAXCN | Cartridge | 1 |
| NQEBXAN | Cartridge | 1 |
| RPGCLAN | Cartridge - Primary | 1 |