



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Check Cracking Pressure	2 bar
Mounting Hole Diameter	10,4 mm
Mounting Hole C'bore Diameter	15,0 mm
Mounting Hole C'bore Depth	8 mm
Mounting Hole Quantity	2

**CONFIGURATION OPTIONS**
**Model Code Example: YFRCLANAL**

CONTROL		(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b>	Standard Screw Adjustment	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	
<b>C</b>	Tamper Resistant - Factory Set	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	<b>V</b> Viton	
<b>J</b>	Capped Screw Adjustment	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
<b>K</b>	manilla	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
		<b>J</b> 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting		
		<b>K</b> 75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar) Standard Setting		
		<b>S</b> 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting		
		<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		

**PRIMARY CARTRIDGE**
**(A)**

<b>A</b>	A (with RPGC primary cartridge, Pilot-operated, pistón balanceado alivio válvula )
<b>A</b>	A (with RPGC3 primary cartridge, No-ajustable pilot-operated, pistón balanceado alivio válvula )
<b>A</b>	A (with RPGC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral )

**INCLUDED COMPONENTS**

Part	Description	Quantity
500-001-113*	O-Ring	2
500-001-125*	O-Ring	1
CXFAXCN	Cartridge	1
NQEBXAN	Cartridge	1
RPGCLAN	Cartridge - Primary	1