



TECHNICAL DATA

Body Type	Line mount
Capacity	15 - 65 L/min.
Mounting Hole Diameter	8.6 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

OPTION SELECTION EXAMPLE: YGDBXANS

CONTROL	(X)	FLOW SPLIT	(A)	SEAL MATERIAL	(N)	ORIFICE PART DESIGNATION	(S)
X Not Adjustable		A 50/50		N Buna-N V Viton		S Slip @ 3000 psi = 9.17 gpm (with FSDH primary cartridge, Alta capacidad , centro cerrado, divisor / combinador de caudal válvula)	
						A Slip @ 3000 psi = 0 gpm (with FSDH primary cartridge, Alta capacidad , centro cerrado, divisor / combinador de caudal válvula)	
						N Slip @ 3000 psi = 3.14 gpm (with FSDH primary cartridge, Alta capacidad , centro cerrado, divisor / combinador de caudal válvula)	
						U Slip @ 3000 psi = 16.21 gpm (with FSDH primary cartridge, Alta capacidad , centro cerrado, divisor / combinador de caudal válvula)	
						Z No Orifice Plug Installed (with FSDH primary cartridge, Alta capacidad , centro cerrado, divisor / combinador de caudal válvula)	