



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	10,7 mm
	Through
	2

CONFIGURATION OPTIONS

Model Code Example: YGEBXANUM

(X)	(A)	(N)	ORIFICE PART DESIGNATION(N)	PORT AND MATERIAL DESIGNATION (M)
X	A 50/50	N V	U Slip @ 3000 psi = 16.21 gpm (with FSEH primary cartridge, , , -) A Slip @ 3000 psi = 0 gpm (with FSEH primary cartridge, , , -) Q Slip @ 3000 psi = 6.31 gpm (with FSEH primary cartridge, , , -) W Slip @ 3000 psi = 25.25 gpm (with FSEH primary cartridge, , , -) Z No Orifice Plug Installed (with FSEH primary cartridge, , , -)	M Ports 2, 3, 4 — SAE 16; Gage Ports (Plugged) — SAE 4; Aluminum) D Ports 2, 3, 4 — 3/4" NPTF; Gage Ports (Plugged) — SAE 4; Aluminum) D/S Ports 2, 3, 4 — 3/4" NPTF; Gage Ports (Plugged) — SAE 4; Iron) E Ports 2, 3, 4 — 1" NPTF; Gage Ports (Plugged) — SAE 4; Aluminum) E/S Ports 2, 3, 4 — 1" NPTF; Gage Ports (Plugged) — SAE 4; Iron L Ports 2, 3, 4 — SAE 12; Gage Ports (Plugged) — SAE 4; Aluminum L/S Ports 2, 3, 4 — SAE 12; Gage Ports (Plugged) — SAE 4; Iron M/S Ports 2, 3, 4 — SAE 16; Gage Ports (Plugged) — SAE 4; Iron W Ports 2, 3, 4 — 3/4" BSPP; Gage Ports (Plugged) — SAE 4; Aluminum W/S Ports 2, 3, 4 — 3/4" BSPP; Gage Ports (Plugged) — SAE 4; Iron X Ports 2, 3, 4 — 1" BSPP; Gage Ports (Plugged) — SAE 4; Aluminum X/S Ports 2, 3, 4 — 1" BSPP; Gage Ports (Plugged) — SAE 4; Iron

INCLUDED COMPONENTS

Part	Description	Quantity
280-038-125*	Orifice	2
A330-006-004*	SAE Plug	2
FSEHXAN	Cartridge - Primary	1