



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	10,7 mm
	Through
	2



**CONFIGURATION OPTIONS**

**Model Code Example: YGFBXANXN**

(X)	(A)	(N)	ORIFICE PART DESIGNATION(X)	PORT AND MATERIAL DESIGNATION (N)
X	A 50/50	N	X Slip @ 3000 psi = 36.67 gpm (with FSFH primary cartridge, , , -	N Ports 2, 3, 4 — SAE 20; Gage Ports (Plugged) — SAE 8; Aluminum
		V	A Slip @ 3000 psi = 0 gpm (with FSFH primary cartridge, , , -	5 Port 3 — 1-1/4" C62; Ports 2 & 4 — 1" Code 62; Gage Ports (Plugged) — SAE 8; Aluminum
			T Slip @ 3000 psi = 12.33 gpm (with FSFH primary cartridge, , , -	5/M Port 3 — 1-1/4" C62; Ports 2 & 4 — 1" Code 62; Gage Ports (Plugged) — SAE 8; Metric Aluminum
			Y Slip @ 3000 psi = 64.85 gpm (with FSFH primary cartridge, , , -	5/S Port 3 — 1-1/4" C62; Ports 2 & 4 — 1" Code 62; Gage Ports (Plugged) — SAE 8; Iron
			Z No Orifice Plug Installed (with FSFH primary cartridge, , , -	5/T Port 3 — 1-1/4" C62; Ports 2 & 4 — 1" Code 62; Gage Ports (Plugged) — SAE 8; Metric Iron
				E Ports 2, 3, 4 — 1" NPTF; Gage Ports (Plugged) — SAE 8; Aluminum
				E/S Ports 2, 3, 4 — 1" NPTF; Gage Ports (Plugged) — SAE 8; Iron
				F Ports 2, 3, 4 — 1 1/4" NPTF; Gage Ports (Plugged) — SAE 8; Aluminum
				F/S Ports 2, 3, 4 — 1 1/4" NPTF; Gage Ports (Plugged) — SAE 8; Iron
				M Ports 2, 3, 4 — SAE 16; Gage Ports (Plugged) — SAE 8; Aluminum
				M/S Ports 2, 3, 4 — SAE 16; Gage Ports (Plugged) — SAE 8; Iron
				N/S Ports 2, 3, 4 — SAE 20; Gage Ports (Plugged) — SAE 8; Iron
				Q Port 3 — 1 1/4" Code 61 ; Ports 2 & 4 — 1" Code 61; Gage Ports (Plugged) — SAE 8; Aluminum
				Q/M Port 3 — 1 1/4" Code 61 ; Ports 2 & 4 — 1" Code 61; Gage Ports (Plugged) — SAE 8; Metric Aluminum

**PORT AND MATERIAL  
DESIGNATION (N)**

- Q/S** Port 3 — 1 1/4" Code 61 ; Ports 2 & 4 — 1" Code 61; Gage Ports (Plugged) — SAE 8; Iron
- Q/T** Port 3 — 1 1/4" Code 61 ; Ports 2 & 4 — 1" Code 61; Gage Ports (Plugged) — SAE 8; Metric Iron
- X** Ports 2, 3, 4 — 1" BSPP; Gage Ports (Plugged) — SAE 8; Aluminum
- X/S** Ports 2, 3, 4 — 1" BSPP; Gage Ports (Plugged) — SAE 8; Iron
- Y** Ports 2, 3, 4 — 1 1/4" BSPP; Gage Ports (Plugged) — SAE 8; Aluminum
- Y/S** Ports 2, 3, 4 — 1 1/4" BSPP; Gage Ports (Plugged) — SAE 8; Iron

**INCLUDED COMPONENTS**

Part	Description	Quantity
280-040-094*	Orifice	2
A330-006-008*	SAE Plug	2
FSFHAN	Cartridge - Primary	1