



TECHNICAL DATA

Body Type	aplilables
Interface	ISO 03
Body Features	descarga regulada en B
Seal Plate Included (see notes)	Yes
Stack Height	44,5 mm

CONFIGURATION

X	Control	Not Adjustable
F	Differential Pressure	100 psi (7 bar)
N	Seal Material	Buna-N
A	Primary Cartridge	A (with LPDC primary cartridge, Normalmente abierto, elementos de modulación)
A	Port and Material Designation	A Aluminum

CONFIGURATION OPTIONS

Model Code Example: YLCBxFNAA

CONTROL	(X)	DIFFERENTIAL PRESSURE	(F)	SEAL MATERIAL	(N)
X	Not Adjustable	F	100 psi (7 bar)	N	Buna-N
		G	150 psi (10,5 bar)	V	Viton
		H	200 psi (14 bar)		

PRIMARY CARTRIDGE

(A)

A	A (with LPDC primary cartridge, Normalmente abierto, elementos de modulación)
A	A (with LPDCL primary cartridge, Ajustable, normalmente abierto, elementos de modulación)

INCLUDED COMPONENTS

Part	Description	Quantity
500-001-012*	O-Ring	4
700-002*	Seal Plate	1
811-001-006*	Pin	1
850-004-250*	Plug	2
CXDAXCN	Cartridge	1
LPDCXFN	Cartridge - Primary	1