



CONFIGURATION

X Control	Not Adjustable
F Differential Pressure	100 psi (7 bar)
N Seal Material	Buna-N
A Primary Cartridge	A (with LPDC primary cartridge, Normalmente abierto, elementos de modulación)
A Port and Material Designation	A Aluminum

TECHNICAL DATA

Body Type	aplilables	NOTE: DATA MAY VARY BY
Interface	ISO 03	
Capacity	60 L/min.	
Body Features	descarga regulada en B	
Seal Plate Included (see notes)	Yes	
Stack Height	44,5 mm	

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: YLCBXFNA

CONTROL	(X) DIFFERENTIAL PRESSURE	(F) SEAL MATERIAL	(N)
X Not Adjustable	F 100 psi (7 bar)	N Buna-N	
	G 150 psi (10,5 bar)	V Viton	
	H 200 psi (14 bar)		

PRIMARY CARTRIDGE (A)

A	A (with LPDC primary cartridge, Normalmente abierto, elementos de modulación)
A	A (with LPDCL primary cartridge, Ajustable, normalmente abierto, elementos de modulación)

INCLUDED COMPONENTS

Part	Description	Quantity
500-001-012*	O-Ring	4
700-002*	Seal Plate	1
811-001-006*	Pin	1
850-004-250*	Plug	2
CXDAXCN	Cartridge	1
LPDCXFN	Cartridge - Primary	1