



**TECHNICAL DATA**

	ISO 03
Stack Height	44,7 mm
( )	
	On A with reverse flow check

**CONFIGURATION**

L	
N	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)
N	
A Primary Cartridge	A (with PBDB primary cartridge, , )
Port and Material Designation	

**CONFIGURATION OPTIONS**

**Model Code Example: YPCALNNA**

	(L)	(N)	(N)
<b>L</b>		<b>N</b> 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	<b>N</b>
<b>C</b>	-	<b>A</b> 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	<b>V</b>
<b>F</b>			
<b>K</b>		<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	
<b>W</b>		<b>C</b> 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar)	
<b>Y</b>		<b>D</b> 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)	
		<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)	
		<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
		<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)	

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	A (with PBDB primary cartridge, , )
<b>A</b>	A (with PBDB8 primary cartridge, , T-8A )