



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	ISO 03
	40 L/min.
Stack Height	44,7 mm
( )	
	On A with reverse flow check

**OPTION SELECTION EXAMPLE: YPCALNNA**

	(L)	(N)	(N)
<b>L</b>	<b>N</b>	60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	<b>N</b>
<b>J</b>	<b>A</b>	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	<b>V</b>
<b>O</b>	<b>B</b>	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	
<b>W</b>	<b>C</b>	150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar)	
	<b>D</b>	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)	
	<b>Q</b>	60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
	<b>W</b>	150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)	

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	A (with PBDB primary cartridge, , )		
<b>A</b>	A (with PBDB8 primary cartridge, ,	T-8A	)