



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

CONFIGURATION OPTIONS

Model Code Example: YPDCLANWNNK

CONTROL (L)	ADJUSTMENT RANGE(N)	MINIMUM CONTROL PRESSURE (W)	SEAL MATERIAL (N)	SEAL MATERIAL (N)	PORT AND MATERIAL DESIGNATION (K)
L Standard Screw Adjustment	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting	W 100 psi (7 bar)	N Buna-N	N Buna-N	K Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Aluminum
C Tamper Resistant - Factory Set	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting	D 25 psi (1,7 bar)	V Viton	V Viton	A Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Aluminum
K manilla	C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) Standard Setting				A/S Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Iron
	D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting				B Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Aluminum
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				B/S Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Iron
					C Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Aluminum
					C/S Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Iron
					I Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Aluminum
					I/S Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Iron
					J Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Aluminum
					J/S Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Iron
					K/S Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Iron
					T Ports 1 & 2 — 1/4" BSPP; Port 3 — 1/4" BSPP; Aluminum
					T/S Ports 1 & 2 — 1/4" BSPP; Port 3 — 1/4" BSPP; Iron
					U Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Aluminum
					U/S Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Iron
					V Ports 1 & 2 — 1/2" BSPP; Port 2 — 1/4" BSPP; Aluminum

**PORT AND MATERIAL
DESIGNATION (K)**

V/S Ports 1 & 2
— 1/2" BSPP;
Port 2 — 1/4"
BSPP; Iron