



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	7,1 mm
	Through
	2

CONFIGURATION OPTIONS

Model Code Example: YPDCLNWNK

(L)	(W)	(N)	(N)	(N)	PORT AND MATERIAL DESIGNATION (K)
L	W 100 psi (7 bar)	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	N	N	K Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Aluminum
O	D 25 psi (1,7 bar)	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	V	V	A Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Aluminum
W		B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)			A/S Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Iron
		C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar)			B Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Aluminum
		D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)			B/S Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Iron
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			C Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Aluminum
		W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)			C/S Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Iron
					I Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Aluminum
					I/S Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Iron
					J Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Aluminum
					J/S Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Iron
					K/S Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Iron
					T Ports 1 & 2 — 1/4" BSPP; Port 3 — 1/4" BSPP; Aluminum
					T/S Ports 1 & 2 — 1/4" BSPP; Port 3 — 1/4" BSPP; Iron
					U Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Aluminum
					U/S Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Iron
					V Ports 1 & 2 — 1/2" BSPP; Port 2 — 1/4" BSPP; Aluminum

**PORT AND MATERIAL
DESIGNATION (K)**

V/S Ports 1 & 2
— 1/2" BSPP;
Port 2 — 1/4"
BSPP; Iron