



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Capacity	80 L/min.
Mounting Hole Diameter	7,1 mm
Mounting Hole Quantity	2

OPTION SELECTION EXAMPLE: YPFALANWNNK

CONTROL	(L)	ADJUSTMENT RANGE(A)	MINIMUM CONTROL PRESSURE (W)	SEAL MATERIAL (N)	SEAL MATERIAL (N)	PORT AND MATERIAL DESIGNATION (K)
L	Standard Screw Adjustment	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting	W 100 psi (7 bar)	N Buna-N	N Buna-N	K Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Aluminum
C	Tamper Resistant - Factory Set			V Viton	V Viton	
J	Capped Screw Adjustment	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting	D 25 psi (1,7 bar)			A Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Aluminum
K	manilla	C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) Standard Setting				A/S Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Iron
		D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting				B Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Aluminum
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				B/S Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Iron
		N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting				C Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Aluminum
		S 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting				C/S Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Iron
						D Ports 1 & 2 — 3/4" NPTF; Port 3 — 1/4" NPTF; Aluminum
						D/S Ports 1 & 2 — 3/4" NPTF; Port 3 — 1/4" NPTF; Iron
						I Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Aluminum
						I/S Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Iron
						J Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Aluminum
						J/S Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Iron
						K/S Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Iron
						U Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Aluminum
						U/S Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Iron
						V Ports 1 & 2 — 1/2" BSPP; Port 3 — 1/4" BSPP; Aluminum

**PORT AND MATERIAL
DESIGNATION (K)**

- V/S** Ports 1 & 2
— 1/2" BSPP;
Port 3 — 1/4"
BSPP; Iron

- W** Ports 1 & 2
— 3/4" BSPP;
Port 3 — 1/4"
BSPP;
Aluminum

- W/S** Ports 1 & 2
— 3/4" BSPP;
Port 3 — 1/4"
BSPP; Iron