



**CONFIGURATION OPTIONS**
**Model Code Example: YPFBLANCK**

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b>	Standard Screw Adjustment	<b>A</b>	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting
<b>C</b>	Tamper Resistant - Factory Set	<b>N</b>	Buna-N
<b>F</b>	Hex Head Screw with Locknut	<b>V</b>	Viton
<b>W</b>	Hex Wrench Adjustment	<b>B</b>	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting
<b>Y</b>	manilla de tres agarres	<b>C</b>	150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) Standard Setting
		<b>D</b>	25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting
		<b>E</b>	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting
		<b>N</b>	60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting
		<b>Q</b>	60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting
		<b>W</b>	150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting

**PRIMARY CARTRIDGE**
**(C)**

<b>C</b>	30 psi (2 bar) (with PBFB primary cartridge, Pilot-operated, reductor de presión válvula )
<b>A</b>	4 psi (0,3 bar) (with PBFB primary cartridge, Pilot-operated, reductor de presión válvula )
<b>B</b>	15 psi (1 bar) (with PBFB primary cartridge, Pilot-operated, reductor de presión válvula )
<b>D</b>	50 psi (3,5 bar) (with PBFB primary cartridge, Pilot-operated, reductor de presión válvula )
<b>E</b>	75 psi (5 bar) (with PBFB primary cartridge, Pilot-operated, reductor de presión válvula )
<b>F</b>	100 psi (7 bar) (with PBFB primary cartridge, Pilot-operated, reductor de presión válvula )
<b>Z</b>	1 psi (0,07 bar) (with PBFB primary cartridge, Pilot-operated, reductor de presión válvula )
<b>Z</b>	1 psi (0,07 bar) (with PBFB8 primary cartridge, Pilot-operated, reductor de presión módulo principal con cavidad de control T-8A integral )
<b>F</b>	100 psi (7 bar) (with PBFB8 primary cartridge, Pilot-operated, reductor de presión módulo principal con cavidad de control T-8A integral )
<b>E</b>	75 psi (5 bar) (with PBFB8 primary cartridge, Pilot-operated, reductor de presión módulo principal con cavidad de control T-8A integral )
<b>D</b>	50 psi (3,5 bar) (with PBFB8 primary cartridge, Pilot-operated, reductor de presión módulo principal con cavidad de control T-8A integral )
<b>C</b>	30 psi (2 bar) (with PBFB8 primary cartridge, Pilot-operated, reductor de presión módulo principal con cavidad de control T-8A integral )
<b>B</b>	15 psi (1 bar) (with PBFB8 primary cartridge, Pilot-operated, reductor de presión módulo principal con cavidad de control T-8A integral )
<b>A</b>	4 psi (0,3 bar) (with PBFB8 primary cartridge, Pilot-operated, reductor de presión módulo principal con cavidad de control T-8A integral )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CXEDXCN	Cartridge	1
PBFBLAN	Cartridge - Primary	1