



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Capacity	80 L/min.
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2



## OPTION SELECTION EXAMPLE: YPFBLANWNNK

CONTROL (L)	ADJUSTMENT RANGE(A)	MINIMUM CONTROL PRESSURE (W)	SEAL MATERIAL (N)	SEAL MATERIAL (N)	PORT AND MATERIAL DESIGNATION (K)
<b>L</b> Standard Screw Adjustment	<b>A</b> 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting	<b>W</b> 100 psi (7 bar)	<b>N</b> Buna-N	<b>N</b> Buna-N	<b>K</b> Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Gage Port — 1/4" NPTF; Aluminum
<b>C</b> Tamper Resistant - Factory Set		<b>D</b> 25 psi (1,7 bar)	<b>V</b> Viton	<b>V</b> Viton	<b>A</b> Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Aluminum
<b>J</b> Capped Screw Adjustment	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting				<b>A/S</b> Ports 1 & 2 — 1/4" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Iron
<b>K</b> manilla	<b>C</b> 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar) Standard Setting				<b>B</b> Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Aluminum
	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar) Standard Setting				<b>B/S</b> Ports 1 & 2 — 3/8" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Iron
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				<b>C</b> Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Aluminum
	<b>N</b> 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting				<b>C/S</b> Ports 1 & 2 — 1/2" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Iron
	<b>S</b> 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting				<b>D</b> Ports 1 & 2 — 3/4" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Aluminum
					<b>D/S</b> Ports 1 & 2 — 3/4" NPTF; Port 3 — 1/4" NPTF; Gage Port — 1/4" NPTF; Iron
					<b>I</b> Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Gage Port — 1/4" NPTF; Aluminum
					<b>I/S</b> Ports 1 & 2 — SAE 6; Port 3 — SAE 6; Gage Port — 1/4" NPTF; Iron

**PORT AND MATERIAL  
DESIGNATION (K)**

---

<b>J</b>	Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Gage Port — 1/4" NPTF; Aluminum
<b>J/S</b>	Ports 1 & 2 — SAE 8; Port 3 — SAE 6; Gage Port — 1/4" NPTF; Iron
<b>K/S</b>	Ports 1 & 2 — SAE 10; Port 3 — SAE 6; Gage Port — 1/4" NPTF; Iron
<b>U</b>	Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Gage Port — 1/4" BSPP; Aluminum
<b>U/S</b>	Ports 1 & 2 — 3/8" BSPP; Port 3 — 1/4" BSPP; Gage Port — 1/4" BSPP; Iron
<b>V</b>	Ports 1 & 2 — 1/2" BSPP; Port 3 — 1/4" BSPP; Gage Port — 1/4" BSPP; Aluminum
<b>V/S</b>	Ports 1 & 2 — 1/2" BSPP; Port 3 — 1/4" BSPP; Gage Port — 1/4" BSPP; Iron
<b>W</b>	Ports 1 & 2 — 3/4" BSPP; Port 3 — 1/4" BSPP; Gage Port — 1/4" BSPP; Aluminum
<b>W/S</b>	Ports 1 & 2 — 3/4" BSPP; Port 3 — 1/4" BSPP; Gage Port — 1/4" BSPP; Iron