



CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)
N	
C	Range Letter(s) of Subordinate Cartridge 30 psi (2 bar) (with PBJB primary cartridge,)
R	Ports 1 & 2 — 1 1/2 in. Code 61; Port 3 — SAE 6; Gage Port — 1/4" NPTF; Aluminum

TECHNICAL DATA

CONFIGURATION OPTIONS

Model Code Example: YPJALANCR

(L)	(A)	(N)
L	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	N
C		V
K	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	
	C 150 - 6000 psi (10,5 - 420 bar), 200 psi (14 bar)	
	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
	W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)	

PRIMARY CARTRIDGE

(C)

C	30 psi (2 bar) (with PBJB primary cartridge, ,)
A	4 psi (0,3 bar) (with PBJB primary cartridge, ,)
B	15 psi (1 bar) (with PBJB primary cartridge, ,)
D	50 psi (3,5 bar) (with PBJB primary cartridge, ,)
E	75 psi (5 bar) (with PBJB primary cartridge, ,)
F	100 psi (7 bar) (with PBJB primary cartridge, ,)
Z	1 psi (0,07 bar) (with PBJB primary cartridge, ,)
Z	1 psi (0,07 bar) (with PBJB8 primary cartridge, , T-8A)
F	100 psi (7 bar) (with PBJB8 primary cartridge, , T-8A)
E	75 psi (5 bar) (with PBJB8 primary cartridge, , T-8A)
D	50 psi (3,5 bar) (with PBJB8 primary cartridge, , T-8A)
C	30 psi (2 bar) (with PBJB8 primary cartridge, , T-8A)
B	15 psi (1 bar) (with PBJB8 primary cartridge, , T-8A)
A	4 psi (0,3 bar) (with PBJB8 primary cartridge, , T-8A)

INCLUDED COMPONENTS

Part	Description	Quantity
CXIDXCN	Cartridge	1
PBJBLAN	Cartridge - Primary	1