



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Capacity	120 L/min.
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

OPTION SELECTION EXAMPLE: YQEALANCK

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	V Viton	
J Capped Screw Adjustment	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
K manilla	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
	W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE (C)

C 30 psi (2 bar) (with SQFB primary cartridge, Tirar-abajo, pilot-operated, pistón balanceado secuencia válvula)
A 4 psi (0,3 bar) (with SQFB primary cartridge, Tirar-abajo, pilot-operated, pistón balanceado secuencia válvula)
B 15 psi (1 bar) (with SQFB primary cartridge, Tirar-abajo, pilot-operated, pistón balanceado secuencia válvula)
D 50 psi (3,5 bar) (with SQFB primary cartridge, Tirar-abajo, pilot-operated, pistón balanceado secuencia válvula)
E 75 psi (5 bar) (with SQFB primary cartridge, Tirar-abajo, pilot-operated, pistón balanceado secuencia válvula)
F 100 psi (7 bar) (with SQFB primary cartridge, Tirar-abajo, pilot-operated, pistón balanceado secuencia válvula)
Z 1 psi (0,07 bar) (with SQFB primary cartridge, Tirar-abajo, pilot-operated, pistón balanceado secuencia válvula)

INCLUDED COMPONENTS

Part	Description	Quantity
CXFAXCN	Cartridge	1
SQFBLAN	Cartridge - Primary	1