



CONFIGURATION OPTIONS
Model Code Example: YRDCLANAJ

CONTROL		(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L	Standard Screw Adjustment	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
C	Tamper Resistant - Factory Set	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	V Viton	
F	Hex Head Screw with Locknut	C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting		
W	Hex Wrench Adjustment	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
Y	manilla de tres agarres	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting		
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting		
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE
(A)

A	A (with RPEC primary cartridge, Pilot-operated, pistón balanceado alivio válvula)
A	A (with RPEC8 primary cartridge, Pilot-operated, pistón balanceado alivio módulo principal con cavidad de control T-8A integral)

INCLUDED COMPONENTS

Part	Description	Quantity
210-010*	Spool	1
230-032*	Sleeve	1
250-022*	Retainer	2
295-002*	Handle	1
300-001-005*	Screw	2
300-002-005*	Screw	1
402-003-075*	Snap Ring	2
500-001-016*	O-Ring	2
515-002-515*	Backup Ring	2
600-052*	Spring	2
800-001-080*	Ball	4
812-001-001*	Pin	1
840-001*	Handle	1
RPECLAN	Cartridge - Primary	3