



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	7,1 mm
	Through
	3

**CONFIGURATION OPTIONS**

**Model Code Example: YRDCLANAJ**

(L)	(A)	(N)
<b>L</b>	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	<b>N</b>
<b>C</b>		<b>V</b>
<b>F</b>	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	
<b>W</b>	<b>C</b> 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)	
<b>Y</b>	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)	
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)	
	<b>N</b> 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)	
	<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
	<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)	

**PRIMARY CARTRIDGE**

(A)

<b>A</b>	A (with RPEC primary cartridge, Pilot-operated, )
<b>A</b>	A (with RPEC8 primary cartridge, Pilot-operated, T-8A )

**INCLUDED COMPONENTS**

Part	Description	Quantity
210-010*	Spool	1
230-032*	Sleeve	1
250-022*	Retainer	2
295-002*	Handle	1
300-001-005*	Screw	2
300-002-005*	Screw	1
402-003-075*	Snap Ring	2
500-001-016*	O-Ring	2
515-002-515*	Backup Ring	2
600-052*	Spring	2
800-001-080*	Ball	4
812-001-001*	Pin	1
840-001*	Handle	1
RPECLAN	Cartridge - Primary	3